

A2 Sub
B1
6. (Amended) A bag according to claim 4, in which only the outside legs of the tag extending beyond the inside legs are sealed to the seal.

7. (Amended) A bag according to claim 4, in which the tag is provided with a line of weakness along the junction of the inside legs of the tag.

A3 Sub
B1
9. (Amended) A bag according to claim 1, in which the tag is made of a laminated material.

A4
12. (Amended) A bag according to claim 1, which has two seals extending parallel to the said margin, one of which is a reclosable zipper seal.

A5 Sub
B1
14. (Amended) A bag according to claim 12, in which the zipper seal has marginal flanges extending laterally from interengageable male and female closure members, and the tag is sealed to the inside surfaces of flanges extending from the closure members towards the mouth of the bag.

A6 Sub
B1
18. (Amended) A method according to claim 15, which includes folding a length of laminated material into a generally M-shaped configuration in cross-section, and cutting off a section of the folded material to form the tag.

A7 Sub
B1
20. (Amended) A method according to claim 15, in which the tag is located on the host material so that the tag lies within the contour of the bag sides when the bag is completed and sealed.

A8 Sub
B1
24. (Amended) Tag material according to claim 21, in which the strip also includes a layer of strengthening material between the first and second layers.

DOCKET NO.: THOM-0014

PATENT

AS 25. (Amended) Tag material according to claim 21, in which the strip also includes a layer of heat insulating material between the first and second layers.

THOMSON